



TECHNICAL DATA

- Size: DN15-DN50
- Maximum working pressure: 10 bar
- Maximum working temperature: +40°C
- Maximum permissible error:
 - In the lower zone: $Q_{min} \dots Q_t: \pm 5\%$
 - In the upper zone: $Q_t \dots Q_s: \pm 2\%$
- Body material: Cast iron

APPLICATION

Distribution water system, cold water.

SPECIFICATION

- Type: Multi jet dry type water meter class B.
- Magnetic drive reliable characteristic.
- Dry dial register ensures anti fog for clear reading.
- ISO 4064 Class B Standard.
- Threaded male BSP cylindrical according to ISO 228-1

Size		DN	15	20	25	32	40	50
		G	3/4"	1"	1"1/4	1"1/2	2"	2"1/2
Norminal flow rate	Q_n	m3/h	1.5	2.5	3.5	6	10	15
Minimum flow rate	Q_{min}	m3/h	0.03	0.05	0.07	0.12	0.20	0.45
Maximum flow rate	Q_s	m3/h	3	5	7	12	20	30
Transitional flow rate	Q_t	m3/h	0.12	0.20	0.28	0.48	0.80	3.00
Minimum reading		m3	0.0001				0.001	
Maximum range		m3	99,999				99,999	

DIMENSIONS

Nominal diameter				
DN (mm)	G	L	H	C
15	3/4"	165	104	99
20	1"	190	106	99
25	1"1/4	225	120	104
32	1"1/2	260	120	104
40	2"	300	155	125
50	2"1/2	300	155	125

Subject to change without prior notice.

ACCURACY CURVE

