



TECHNICAL DATA

- Size : DN50-DN300
- Maximum working pressure : 16 bar
(25 bar on request)
- Maximum working temperature: +120°C
- Testing pressure : Body: 24 bar

MATERIAL

No.	Parts name	Materials
1	Body	Ductile iron EN-GJS-400-15
2	Screen	Stainless steel 304
3	Body gasket	Graphite
4	Bolt	Galvanized steel
5	Cover	Ductile iron EN-GJS-400-15
6	Plug	Stainless steel 201

APPLICATION

Water supply system, fire - fighting, air - conditioning, irrigation, pump station.

SPECIFICATION

- Type: Y- Strainer with stainless steel screen
- Face to face is according to DIN EN 558-1
- Flanges drilled according to EN 1092-2
- Pressure test according to EN 12266-1

DIMENSIONS

Size		L	H	b	D	n-d
DN	Inch					
50	2	230	153	19	165	4-19
65	2-1/2	290	183	19	185	4-19
80	3	310	219	19	200	8-19
100	4	350	238	19	220	8-19
125	5	400	279	19	250	8-19
150	6	480	315	19	285	8-23
200	8	600	400	20	340	12-23
250	10	730	482	22	405	12-28
300	12	850	565	24.5	460	12-28

Subject to change without prior notice.