



**TECHNICAL DATA**

- Size : DN50-DN300
- Maximum working pressure : 16 bar
- Maximum working temperature: +110°C
- Testing pressure : Body: 24 bar  
Seat: 17.6 bar

**MATERIAL**

No.	Parts name	Material
1	Body	Ductile iron GGG50
2	Disc	Ductile iron GGG50
3	Pin	Stainless steel 201
4	Seat	EPDM
5	Shaft	Stainless steel 416
6	Bushing	PTFE
7	O Ring	NBR
8	Handle	Ductile iron

**APPLICATION**

Water supply, fire - fighting, HVAC, cooling and sewage system.

**SPECIFICATION**

- Type: Wafer type butterfly valve with handle
- Face to face is according to DIN 3202
- Mounting flange: ISO 5211
- Between flanges drilled according to EN 1092-2
- Pressure test according to EN 12266-1
- Painting: epoxy power coating
- Operation: handwheel, gear box, electric actuator and pneumatic actuator, limit switch, etc.

**DIMENSIONS**

Size		A	B	C	D1	L	n-d
DN	Inch						
50	2	161	80	42	125	32	4-19
65	2-1/2	175	89	44.7	145	32	4-19
80	3	181	95	45.2	160	32	8-19
100	4	200	114	52.1	180	32	8-19
125	5	213	127	54.4	210	32	8-19
150	6	226	139	55.8	240	32	8-23
200	8	260	175	60.6	295	45	12-23
250	10	292	203	65.6	355	45	12-28
300	12	337	242	76.9	410	45	12-28