



**TECHNICAL DATA**

- Size : DN50-DN600
- Maximum working pressure : 16 bar

**MATERIAL**

No.	Parts name	Materials
1	Body	Ductile iron
2	End ring	Ductile iron
3	Gasket	EPDM
4	Screw	Galvanized carbon steel

**APPLICATION**

Water supply and drainage, water treatment and water network.

**SPECIFICATION**

- Type: Universal Flange Adaptor
- Flanges drilled according to EN 1092
- Pressure test according to EN 12266-1
- Painting: epoxy power coating EN 30677

**DIMENSIONS**

DN	Range	M x L	H	D
50	59-72	M12x120	72	165
65	72-85	M12x120	75	185
80	88-103	M12x130	76	200
100	109-128	M12x130	75	220
125	132-146	M12x130	75	250
150	159-182	M12x130	76	285
200	192-210	M12x130	85	340
200	218-235	M12x130	76	340
250	250-267	M12x140	92	405
250	272-289	M12x140	90	405
300	315-332	M12x140	91	480
350	351-378	M16x180	111	520
400	400-429	M16x180	120	580
450	476-493	M16x180	115	640
500	500-532	M16x180	123	715
600	600-630	M16x180	135	840
600	630-647	M16x180	135	840