



TECHNICAL DATA

- Size : DN40-DN600
- Maximum working pressure : 10 bar/16 bar

MATERIAL

No.	Parts name	Materials
1	End ring	Ductile iron
2	Body	Ductile iron
3	Screw	Galvanized carbon steel
4	Gasket	EPDM

APPLICATION

Water supply and drainage, water treatment and water network.

SPECIFICATION

- Type: Universal Coupling
- Flanges drilled according to EN 1092
- Pressure test according to EN 12266-1
- Painting: epoxy power coating EN 30677

DIMENSIONS

DN	Range	M x L	D	D1	H
40	48-60	12x180	146	64	102
50	59-72	12x180	155	76	102
65	72-85	12x180	172	90	102
80	88-103	12x180	186	107	102
100	109-128	12x190	212	130	102
125	132-146	12x200	248	150	102
150	159-182	12x200	275	186	102
175	192-210	12x220	302	217	130
200	218-235	12x220	325	238	130
225	250-267	12x220	365	273	130
250	272-289	12x220	385	293	130
300	315-332	12x230	440	336	130
350	351-378	16x260	516	382	150
400	400-429	16x260	570	435	150
450	455-472	16x260	605	476	150
500	500-532	16x260	668	540	150
600	600-630	16x260	777	640	150
600	630-647	16x260	790	655	150